

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH, EAST, AND NORTH BOUNDARIES,

AND A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 12, 13, 23, 24, 25, AND 35,

AND

THE DEPENDENT RESURVEY OF A PORTION OF THE RIGHT-OF-WAY LINES OF

UTAH STATE ROAD NO. 196,

IN

**TOWNSHIP 2 SOUTH, RANGE 8 WEST**

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Daniel T. Gillins*  
*Survey Technician*

*Under the Supervision of*

*Ronald K. Baugh*  
*Cadastral Surveyor*

Under Special Instructions dated **August 28, 2007**, approved **August 28, 2007**, which provided for the surveys included under Group Number **1053**, and Assignment Instructions dated **August 28, 2007**.

Survey commenced **August 29, 2007**  
Survey completed **September 27, 2007**

# INDEX DIAGRAM

Township 2 South, Range 8 West

				11	10
6	5	4	3	29 2	21 1 9
7	8	9	10	29	21
				28 11	20 12 8
18	17	16	15	28	19
				27 14	18 13 6
19	20	21	22	26	16
				26 23	15 24 5
30	29	28	27	25	15
				24 26	14 25 4
31	32	33	34	23	13
				22 35	12 36
				3	

The Subdivision of Section 12.....	Page 30
The Subdivision of Section 13.....	Page 32
The Subdivision of Section 23.....	Page 35
The Subdivision of Section 24.....	Page 37
The Subdivision of Section 25.....	Page 39
The Subdivision of Section 35.....	Page 41

The Dependent Resurvey of a portion of the right-of-way lines of Utah State Road No. 196.....	Page 44
--	---------

## TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the south, east and north boundaries, and a portion of the subdivisional lines, the subdivision of sections 12, 13, 23, 24, 25, and 35, and the dependent resurvey of a portion of the right-of-way lines of Utah State Road No. 196, in Township 2 South, Range 8 West, Salt Lake Meridian, Utah.

History of Surveys				
Surveyed by			Retr. or Resurveyed by	
SOUTH BOUNDARY				
All	J. Gorlinski	1871		
Portion			A.J. Stookey	1906
Portion			R.K. Baugh	2004
EAST BOUNDARY				
All	J. Gorlinski	1871		
Portion			R.K. Baugh	2004
WEST BOUNDARY (Guide Meridian)				
All	J. Gorlinski	1871		
All			A.J. Stookey	1906
NORTH BOUNDARY				
All	J. Gorlinski	1871		
All			A.J. Stookey	1906
SUBDIVISION				
Portion	J. Gorlinski	1877		
Portion	A.J. Stookey	1906	A.J. Stookey	1906
RIGHT-OF-WAY SURVEY				
State Road No. 196	State of Utah	1951		

## TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1053, dated August 28, 2007.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Cadastral Control Network was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): KENNECOTT1UT2005 CORS ARP, SALT LAKE CITY CORS ARP, and MIDVALE CORS ARP.

The geographic position of the corner of sections 2, 3, 34, and 35, on the south boundary of the township as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 40°35'35.628" N.,  
Longitude: 112°43'26.765" W., N.A.D. 1983,  
Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

---

Dependent Resurvey of a Portion of the South Boundary,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. Gorlinski in 1871.

---

Beginning at the 1/4 section corner of sections 2 and 35, on the south boundary of the township, monumented with a quartzite stone, 14 X 9 X 3 inches, firmly set, plainly marked 1/4 on N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
S 35  
1/4 —————  
S 2  
T 3 S  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the north side of the aluminum post.

N. 88°54.8' W., between sections 2 and 35.

20.110 Point for the W 1/16 section corner of sections 2 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

S 35  
W 1/16 —————  
S 2  
2007

Set a steel fence post along the east side of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.220 The corner of sections 2, 3, 34, and 35, monumented with a quartzite stone, 18 X 10 X 9 inches, firmly set, projecting 10 inches above the ground, plainly marked with 2 notches on the E. edge and 4 notches on the W. edge; with a mound of stone 3 ft. base, 1 ft. high, 2 links north.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 2 S R 8 W

S 34	S 35
S 3	S 2
T 3 S	
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Rebuild the mound of stone, 3 ft. base, 12 inches high, 3.5 links north of corner.

Corner is located 7.2 links south of a barbed wire fence, bears east and west.

---

Dependent Resurvey of a Portion of the East Boundary,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed  
by J. Gorlinski in 1871.

---

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, monumented with an aluminum post, 2 1/2 inches in diameter, set in a mound of stone, 3 ft. base, to top, with aluminum cap marked as described in the official record of the 2004 resurvey.

N. 0°13.1' E., between sections 25 and 30.

- 40.178 The 1/4 section corner of sections 25 and 30, monumented with a quartzite stone, 19 X 12 X 10 inches, firmly set, plainly marked 1/4 on W. face, from which the 1871 bearing tree:

A cedar, 12 inches in diameter, bears S. 51°15' E., 48 links distance, with blaze and illegible scribing.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 2 S  
R 8 W R 7 W  
1/4  
S 25 | S 30  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the west side of the aluminum post.

---

N. 0°13.9' E., beginning new measurement.

**40.163** The corner of sections 19, 24, 25, and 30, monumented with a quartzite stone, 16 X 12 X 6 inches, firmly set, plainly marked with 2 notches on the S. edge and 4 notches on the N. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 16 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top, with aluminum cap marked:

T 2 S  
R 8 W R 7 W  
  
S 24 | S 19  
S 25 | S 30  
  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the east side of the aluminum post.

---

N. 0°01.4' E., between sections 19 and 24.

**40.113** The 1/4 section corner of sections 19 and 24, monumented with a quartzite stone, 16 X 9 X 7 inches, firmly set, plainly marked 1/4 on W. face, with a scattered mound of stone 2 links west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 2 S  
R 8 W R 7 W  
1/4  
S 24 | S 19  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Rebuild the mound of stone, 2 ft. base, 1 1/2 ft. high, 2 links west of corner.

Set a steel fence post along the west side of the aluminum post.

---

N. 0°05.7' E., beginning new measurement.

40.223 The corner of sections 13, 18, 19, and 24, monumented with a quartzite stone, 16 X 15 X 7 inches, firmly set, plainly marked with 3 notches on the S. edge and 3 notches on the N. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top, with aluminum cap marked:

T 2 S  
R 8 W R 7 W  
S 13 | S 18  
S 24 | S 19  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the NW side of the aluminum post.

---

N. 0°07.4' E., between sections 13 and 18.

40.132 The 1/4 section corner of sections 13 and 18, monumented with a quartzite stone, 20 X 21 X 20 inches, set on top of a rock bed, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 30 inches in rock bed, with aluminum cap marked:



CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

T 2 S  
R 8 W R 7 W  
1/4  
S 13 | S 18  
2007

Deposit the marked stone along the west side of the aluminum post.

Corner is located in a quartzite rock bed that extends east and west.

---

N. 0°02.6' W., beginning new measurement.

19.994 Point for the N 1/16 section corner of sections 13 and 18.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 20 inches in the ground, in a mound of stone, 3 ft. base to top, with aluminum cap marked:

T 2 S  
R 8 W R 7 W  
N 1/16  
S 13 | S 18  
2007

Set a steel fence post along the NW side of the aluminum post.

22.375 Intersect the center line of Utah State Road No. 196, bears NE-SW.

39.988 The corner of sections 7, 12, 13, and 18, monumented with a quartzite stone, 16 X 10 X 6 inches, firmly set, plainly marked with 4 notches on the S. edge and 2 notches on the N. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 2 S  
R 8 W R 7 W  
S 12 | S 7  
S 13 | S 18  
2007

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Bury the marked stone, inverted, alongside the aluminum post.

Corner is located under a wood fence for a corral, bears north and south, and 4.5 ft. south of a fence corner for fences extending east and south.

N.  $0^{\circ}32.4'$  E., between sections 7 and 12.

40.173 The  $1/4$  section corner of sections 7 and 12, monumented with a quartzite stone, 12 X 7 X 5 inches, firmly set, plainly marked  $1/4$  on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2  $1/2$  inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S  
R 8 W R 7 W  
 $1/4$   
S 12 | S 7  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the north side of the aluminum post.

Corner is located 9.5 ft. east of a barbed wire fence, bears north and south.

N.  $0^{\circ}07.4'$  E., beginning new measurement.

20.053 Point for the N  $1/16$  section corner of sections 7 and 12.

Set an aluminum post, 30 inches long, 2  $1/2$  inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S  
R 8 W R 7 W  
N  $1/16$   
S 12 | S 7  
2007

Corner is located 17 inches south of a barbed wire fence, bears east and west, and 4.5 ft. east of a barbed wire fence, bears north and south.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.106 The corner of sections 1, 6, 7, and 12, perpetuated and recorded by Nolan C. Hathcock, Registered Land Surveyor No. 166346, in 2003, remonumented with an iron post, 2 inches in diameter, firmly set, projecting 7 inches above the ground, with brass cap, 3 inches in diameter, marked:

TOOELE COUNTY SURVEYOR

T 2 S

R 8 W	S 1	S 6	R 7 W
	S 12	S 7	
	2003		

**Note:** Mr. Hathcock determined the corner position at the position of a marked stone as per the Utah Land Survey Monument Record sheet on file with the Tooele County Surveyor's Office. This point is accepted as a careful and faithful perpetuation of the original corner position.

Corner is located 9 inches west of a barbed wire fence, bears north and south.

N. 0°19.6' E., between sections 1 and 6.

- 40.002 The 1/4 section corner of sections 1 and 6, perpetuated and recorded by Nolan C. Hathcock, Registered Land Surveyor No. 166346, in 2003, remonumented with an iron post, 2 inches in diameter, firmly set, projecting 8 inches above the ground, with brass cap, 3 inches in diameter, marked:

TOOELE COUNTY SURVEYOR

T 2 S

R 8 W	S 1	S 6	R 7 W
	R 1/4		
	2003		

**Note:** Mr. Hathcock determined the corner position at the position of a marked stone as per the Utah Land Survey Monument Record sheet on file with the Tooele County Surveyor's Office. This point is accepted as a careful and faithful perpetuation of the original corner position.

Corner is located under barbed wire fence, bears north and south.

N. 0°18.5' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.020 The corner of Townships 1 and 2 South, Ranges 7 and 8 West, perpetuated and recorded by Nolan C. Hathcock, Registered Land Surveyor No. 166346, in 2003, remonumented with an iron post, 2 inches in diameter, firmly set, projecting 8 inches above the ground, with brass cap, 3 inches in diameter, marked:

TOOELE COUNTY SURVEYOR

T 1 S

R 8 W	S 36	S 31	R 7 W
R 8 W	S 1	S 6	R 7 W
	T 2 S		
	2003		

**Note:** Mr. Hathcock determined the corner position at the center of a mound of stone along the northwest side of an ancient fence corner for fences running south and east as per the Utah Land Survey Monument Record sheet on file with the Tooele County Surveyor's Office. Mr. Hathcock did not identify the original stone monument, but we found the said stone, a blue quartzite, firmly set along the northwest side of the iron post, 14 X 14 X 7 inches above ground, plainly marked with 6 notches on S., E., W., and N. edges. This point is therefore accepted as a careful and faithful perpetuation of the original corner position.

---

Dependent Resurvey of a Portion of the North Boundary,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed  
by J. Gorlinski in 1871 and  
the Resurvey Executed by A.J. Stookey in 1906.

---

N. 89°45.1'W., between sections 1 and 36.

- 40.049 Point for the 1/4 section corner of sections 1 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 30 inches in the ground, with aluminum cap marked:

T 1 S R 8 W  
S 36  
1/4 —————  
S 1  
T 2 S  
2007

Set a steel fence post along the east side of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

80.098 The corner of sections 1, 2, 35, and 36, monumented with a decayed limestone, 18 X 9 X 5 inches, firmly set, projecting 8 inches above the ground. The stone is too decayed to read any marks.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 1 S R 8 W
S 35   S 36
S 2   S 1
T 2 S
2007

Bury the stone, inverted, alongside the aluminum post.

Set a steel fence post along the west side of the aluminum post.

N. 89°47.4'W., between sections 2 and 35.

40.045 The 1/4 section corner of sections 2 and 35, monumented with a limestone, 12 X 7 X 5 inches, projecting 1 inch above the ground, plainly marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 1 S R 8 W
S 35
1/4 —————
S 2
T 2 S
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the south side of the aluminum post.

N. 89°48.2' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

40.073 The corner of sections 2, 3, 34, and 35, monumented with a limestone, 18 X 7 X 5 inches, firmly set, projecting 5 inches above the ground, plainly marked with 2 notches on E. edge and 4 notches on W. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 1 S R 8 W	
S 34	S 35
S 3	S 2
T 2 S	
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the east side of the aluminum post.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. Gorlinski in 1877.

---

From the 1/4 section corner of sections 35 and 36, monumented with a limestone, 16 X 10 X 7 inches, lying on E. face, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
1/4	
S 35	S 36
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the north side of the aluminum post.

N. 0°08.2'E., between sections 35 and 36.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

20.159 Point for the N 1/16 section corner of sections 35 and 36, not monumented.

40.318 The corner of sections 25, 26, 35, and 36, monumented with a limestone, 14 X 12 X 10 inches, firmly set, projecting 5 inches above the ground, plainly marked with 1 notch on S. edge and 1 notch on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W			
S 26	S 25		
S 35	S 36		
2007			

Bury the marked stone, inverted, alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, 2 links north of corner.

Corner is located under a barbed wire fence, bears east and west.

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

N. 89°20.3' W., between sections 25 and 36.

40.331 Point for the 1/4 section corner of sections 25 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
S 25	
1/4	
	S 36
2007	

Corner is located 12 ft. south of a barbed wire fence, bears east and west.

80.662 The corner of sections 25, 26, 35, and 36.

N. 0°03.5' E., between sections 25 and 26.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

25.135 Intersect the center line of Utah State Road No. 196, bears NE-SW.

40.201 The 1/4 section corner of sections 25 and 26, monumented with a limestone, 10 X 9 X 7 inches, firmly set, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
1/4	
S 26	S 25
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Corner is located at a fence corner with barbed wire fences extending north and east.

---

N. 0°13.7' E., beginning new measurement.

40.416 The corner of sections 23, 24, 25, and 26, monumented with a limestone, 16 X 12 X 7 inches, firmly set, plainly marked with 2 notches on S. edge and 1 notch on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
S 23   S 24	
S 26   S 25	
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Corner is located at a fence corner, with barbed wire fences extending south and west.

---

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

N. 89°16.2' W., between sections 24 and 25.



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.911 The 1/4 section corner of sections 24 and 25, monumented with a quartzite stone, 18 X 8 X 7 inches, lying on S. face in a scattered mound of stone, plainly marked 1/4 on N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
S 24  
1/4 —————  
S 25  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the west side of the aluminum post.

---

N. 89°01.2' W., beginning new measurement.

- 18.368 Intersect the center line of Utah State Road No. 196, bears NE-SW.

- 20.425 Point for the W 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

S 24  
W 1/16 —————  
S 25  
2007

Set a steel fence post along the east side of the aluminum post.

Corner is located 25 ft. west of a wired fence, bears north and south.

- 40.850 The corner of sections 23, 24, 25, and 26.

---

N. 0°14.9' E., between sections 23 and 24.

- 20.118 Point for the S 1/16 section corner of sections 23 and 24, not monumented.

- 40.236 The 1/4 section corner of sections 23 and 24, monumented with a decayed and fragmented limestone, buried 1 inch below the ground. The fragments make up a stone, 15 X 8 X 4 inches, plainly marked 1/4.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
1/4  
S 23 | S 24  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Corner is located under a barbed wire fence, bears east and west.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

N. 89°00.2' W., between sections 13 and 24.

20.117 Point for the E 1/16 section corner of sections 13 and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 22 inches in the ground, in a mound of stone, 2 ft. base to top, with aluminum cap marked:

S 13  
E 1/16 —————  
S 24  
2007

Set a steel fence post along the south side of the aluminum post.

24.658 Point of intersection with the southeasterly right-of-way line of Utah State Road No. 196, hereinafter described.

25.473 Intersect the center line of Utah State Road No. 196, bears NE-SW.

40.234 Point for the 1/4 section corner of sections 13 and 24, determined latitudinally by an ancient cedar post fence line extending east and west, and longitudinally by proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 2 S R 8 W  
S 13  
1/4 —————  
S 24  
2007

Set a steel fence post along the east side of the aluminum post.

---

N. 89°14.9' W., beginning new measurement.

20.115 Point for the W 1/16 section corner of sections 13 and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

S 13  
W 1/16 —————  
S 24  
2007

Corner is located 2 ft. west of a N-S barbed wire fence, 6.8 ft. south of a mound of stone, 3 ft. base, 1 1/2 ft. high, and 18.9 ft. south of an E-W barbed wire fence.

40.230 The corner of sections 13, 14, 23, and 24, monumented with a limestone, 16 X 10 X 6 inches, lying on W. face, plainly marked with 3 notches on S. edge and 1 notch on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
S 14 | S 13  
S 23 | S 24  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Corner is located under a barbed wire fence, bears east and west.

---

N. 0°19.1' E., between sections 13 and 14.

20.071 Point for the S 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

S 1/16	
S 14	S 13
2007	

Corner is located 2.5 ft. north of a mound of stone, 3 ft. base, 1 1/2 ft. high, and 2.5 ft. west of a barbed wire fence, bears north and south.

- 40.142** The 1/4 section corner of sections 13 and 14, monumented with a quartzite stone, 15 X 10 X 5 inches, lying on E. face in a scattered mound of stone, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, in a mound of stone, 3 ft. base, 6 inches high, with aluminum cap marked:

T 2 S R 8 W	
1/4	
S 14	S 13
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located at a fence corner with barbed wire fences extending south and east.

---

**N. 0°18.2' E.**, beginning new measurement.

- 40.036** The corner of sections 11, 12, 13, and 14, monumented with a quartzite stone, 15 X 8 X 7 inches, firmly set in scattered mound of stone, projecting 5 inches above the ground, plainly marked with 4 notches on S. edge and 1 notch on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, in a mound of stone, 3 ft. base to top, with aluminum cap marked:

T 2 S R 8 W	
S 11	S 12
S 14	S 13
2007	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the east side of the aluminum post.

---

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

N. 88°50.6' W., between sections 12 and 13.

20.043 Point for the E 1/16 section corner of sections 12 and 13, not monumented.

40.086 The 1/4 section corner of sections 12 and 13, monumented with a limestone, 15 X 10 X 5 inches, lying on S. face, dimly marked 1/4 on N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
S 12  
1/4 —————  
S 13  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the south side of the aluminum post.

---

N. 89°19.0' W., beginning new measurement.

19.991 Point for the W 1/16 section corner of sections 12 and 13.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

S 12  
W 1/16 —————  
S 23  
2007

Set a steel fence post along the south side of the aluminum post.

39.982 The corner of sections 11, 12, 13, and 14.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

---

N. 0°17.4' E., between sections 11 and 12.

- 39.923 The 1/4 section corner of sections 11 and 12, monumented with a quartzite stone, 12 X 10 X 6 inches, lying on W. face, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W		
1/4		
S 11		S 12
2007		

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the west side of the aluminum post.

---

N. 0°19.1' E., beginning new measurement.

- 19.948 Point for the N 1/16 section corner of sections 11 and 12, not monumented.

- 39.896 The corner of sections 1, 2, 11, and 12, monumented with decayed and fragmented limestone. The largest piece is 12 X 10 X 6 inches. The stone is too decayed to read any marks.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, in a mound of stone that includes the fragments of the original stone monument, with aluminum cap marked:

T 2 S R 8 W		
<hr/>		
S 2		S 1
S 11		S 12
<hr/>		
2007		

Set a steel fence post along the east side of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

---

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, hereinbefore described.

N. 89°22.0' W., between sections 1 and 12.

- 39.905 The 1/4 section corner of sections 1 and 12, monumented with a limestone, 16 X 8 X 5 inches, lying on S. face, plainly marked 1/4 on N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
S 1  
1/4 —————  
S 12  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the west side of the aluminum post.

---

N. 89°27.1' W., beginning new measurement.

- 20.091 Point for the W 1/16 section corner of sections 1 and 12, not monumented.
- 40.182 The corner of sections 1, 2, 11, and 12.

---

N. 0°19.3' E., between sections 1 and 2.

- 40.225 The 1/4 section corner of sections 1 and 2, monumented with a quartzite stone, 9 X 8 X 5 inches, lying on E. face, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
1/4  
S 2 | S 1  
2007

Bury the marked stone, inverted, alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post along the east side of the aluminum post.

---

N. 0°16.2' E., beginning new measurement.

- 39.319 The corner of sections 1, 2, 35, and 36, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, hereinbefore described.

N. 0°15.6' E., between sections 34 and 35.

- 20.084 Point for the S 1/16 section corner of sections 34 and 35, not monumented.

- 40.168 The 1/4 section corner of sections 34 and 35, monumented with a quartzite stone, 10 X 8 X 8 inches, firmly set, projecting 1 inch above the ground, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

```

      T 2 S R 8 W
        1/4
      S 34 | S 35
        2007
  
```

Bury the marked stone, inverted, alongside the aluminum post.

---

N. 0°15.7' E., beginning new measurement.

- 40.250 The corner of sections 26, 27, 34, and 35, monumented with a quartzite stone, 14 X 8 X 6 inches, loosely set, plainly marked with 1 notch on S. edge.

At the corner point



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
S 27	S 26
S 34	S 35

2007

Bury the marked stone, inverted, alongside the aluminum post.

---

From the corner of sections 25, 26, 35, and 36.

S. 89°54.1' W., between sections 26 and 35.

- 11.004 Point of intersection with the southeasterly right-of-way line of Utah State Road No. 196, hereinafter described.
- 12.743 Intersect the center line of Utah State Road No. 196, bears NE-SW.
- 14.481 Point of intersection with the northwesterly right-of-way line of Utah State Road No. 196, hereinafter described.
- 19.987 Point for the E 1/16 section corner of sections 26 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

	S 26
E 1/16	S 35
	2007

Set a steel fence post along the east side of the aluminum post.

Corner is located 29 ft. west of a drainage, course NW.

- 39.974 Point for the 1/4 section corner of sections 26 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
	S 26
1/4	S 35
	2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post along the north side of the aluminum post.

79.948 The corner of sections 26, 27, 34, and 35.

---

N. 0°18.3' E., between sections 26 and 27.

40.265 The 1/4 section corner of sections 26 and 27, monumented with a quartzite stone, 14 X 7 X 5 inches, marked 1/4 on W. face, firmly set alongside an old cedar post, 6 inches square, projecting 5 ft. above ground.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
1/4	
S 27	S 26
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the west side of the aluminum post.

Corner is located 294 ft. south of a new wire mesh fence, bears NW and SE.

---

N. 0°17.7' E., beginning new measurement.

40.256 The corner of sections 22, 23, 26, and 27, monumented with a quartzite stone, 13 X 6 X 6 inches, lying on N. face, plainly marked with 2 notches on S. edge and 2 notches on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
S 22	S 23
S 27	S 26
2007	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the NW side of the aluminum post.

From the corner of sections 23, 24, 25, and 26.

N.  $89^{\circ}28.9'$  W., between sections 23 and 26.

20.104 Point for the E  $1/16$  section corner of sections 23 and 26.

Set an aluminum post, 30 inches long, 2  $1/2$  inches in diameter, 28 inches in the ground, with aluminum cap marked:

	S 23
E $1/16$	—————
	S 26
	2007

Set a steel fence post alongside the aluminum post.

40.208 The  $1/4$  section corner of sections 23 and 26, monumented with a quartzite stone, 18 X 12 X 8 inches, lying on N. face, plainly marked  $1/4$  on N. face, with an old cedar post, 6 ft. long, 3 inches in diameter, lying alongside.

At the corner point

Set an aluminum post, 30 inches long, 2  $1/2$  inches in diameter, 26 inches in the ground, with aluminum cap marked:

	T 2 S R 8 W
	S 23
$1/4$	—————
	S 26
	2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the north side of the aluminum post.

Re-set the old cedar post along the NW side of the aluminum post.

S.  $89^{\circ}08.0'$  W., beginning new measurement.

39.508 The corner of sections 22, 23, 26, and 27.

N.  $0^{\circ}18.2'$  E., between sections 22 and 23.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

- 40.297 The 1/4 section corner of sections 22 and 23, monumented with a quartzite stone, 13 X 13 X 5 inches, firmly set, projecting 1 inch above ground, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
1/4	
S 22	S 23
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the south side of the aluminum post.

---

N. 0°16.1' E., beginning new measurement.

- 40.200 The corner of sections 14, 15, 22, and 23, monumented with a quartzite stone, 14 X 13 X 8 inches, firmly set, projecting 8 inches above the ground, dimly marked, with an old cedar post, 3 inches in diameter, rotted at base, set alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W	
S 15	S 14
S 22	S 23
2007	

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the SW side of the aluminum post.

---

From the corner of sections 13, 14, 23, and 24.

S. 89°55.5' W., between sections 14 and 23.

- 39.773 The 1/4 section corner of sections 14 and 23, monumented with a quartzite stone, 13 X 9 X 4 inches, lying on S. face, marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

1/4 on N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
S 14  
1/4 —————  
S 23  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Corner is located at a fence corner with barbed wire fences extending east and south.

---

S. 89°56.4' W., beginning new measurement.

39.881 The corner of sections 14, 15, 22, and 23.

---

N. 0°18.6' E., between sections 14 and 15.

40.216 Point for the 1/4 section corner of sections 14 and 15, at proportionate distance, falls in swampy ground where it is unsuitable for monumentation; there is no remaining evidence of the original corner.

80.432 The corner of sections 10, 11, 14, and 15, monumented with a quartzite stone, 14 X 10 X 5 inches, buried 5 inches below the ground, marked with 4 notches on S. edge and 2 notches on E. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
  
S 10 | S 11  
S 15 | S 14  
  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the east side of the aluminum post.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 11, 12, 13, and 14.

S. 89°51.3' W., between sections 11 and 14.

- 39.303 The 1/4 section corner of sections 11 and 14, monumented with a quartzite stone, 15 X 8 X 5 inches, lying on N. face, marked 1/4 on N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
S 11  
1/4 —————  
S 14  
2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the NW side of the aluminum post.

---

N. 89°37.7' W., beginning new measurement.

- 40.335 The corner of sections 10, 11, 14, and 15.

---

N. 0°26.4' E., between sections 10 and 11.

- 40.347 Point for the 1/4 section corner of sections 10 and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
1/4  
S 10 | S 11  
2007

Set a steel fence post along the east side of the aluminum post.

- 80.694 The corner of sections 2, 3, 10, and 11, monumented with a quartzite stone, 15 X 7 X 7 inches, lying on E. face, marked with 5 notches on S. edge; with a decayed cedar post stump set alongside.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S R 8 W

S 3	S 2
S 10	S 11

2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post along the west side of the aluminum post.

From the corner of sections 1, 2, 11, and 12.

N. 88°52.2' W., between sections 2 and 11.

- 39.171 The 1/4 section corner of sections 2 and 11, monumented with a decayed quartzite stone, 11 X 11 X 5 inches, firmly set, projecting 1 inch above ground. The stone is too decayed to read any marks.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
S 2  
1/4 —————  
S 11  
2007

Bury the stone, inverted, alongside the aluminum post.

Set a steel fence post along the NE side the aluminum post.

N. 89°37.6' W., beginning new measurement.

- 40.261 The corner of sections 2, 3, 10, and 11.

N. 0°13.1' W., between sections 2 and 3.

- 39.496 Point for the 1/4 section corner of sections 2 and 3, at proportionate distance, there is no evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches in

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH  
CHAINS

diameter, 30 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
1/4  
S 3 | S 2  
2007

Set a steel fence post along the south side of the aluminum post.

Corner is located in grassy area 40 ft. east of a swamp.

78.794 The corner of sections 2, 3, 34, and 35, on the north boundary of the township, hereinbefore described.

---

The Subdivision of Section 12,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 12 and 13.

N. 0°27.2' E., on the N-S center line of section 12.

39.884 Point for the center 1/4 section corner of section 12 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
C 1/4 S 12  
2007

Set a steel fence post along the NE side the aluminum post.

59.898 Point for the center N 1/16 section corner of section 12.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

C  
N 1/16 | S 12  
C  
2007



THE SUBDIVISION OF SECTION 12,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post along the north side of the aluminum post.

79.912 The 1/4 section corner of sections 1 and 12.

---

From the 1/4 section corner of sections 7 and 12, on the east boundary of the township, hereinbefore described.

N. 89°15.5' W., on the E-W center line of section 12.

40.141 The center 1/4 section corner of section 12.

60.187 Point for the center W 1/16 section corner of section 12.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

W 1/16  
C ————— C  
S 12  
2007

Set a steel fence post along the SW side the aluminum post.

80.233 The 1/4 section corner of sections 11 and 12.

---

From the N 1/16 section corner of sections 7 and 12, on the east boundary of the township, hereinbefore described.

N. 89°18.6' W., on the E-W center line of the NE 1/4 of section 12.

40.023 The center N 1/16 section corner of section 12.

---

From the W 1/16 section corner of sections 12 and 13.

N. 0°22.3' E., on the N-S center line of the SW 1/4 of section 12.

39.904 The center W 1/16 section corner of section 12.

---

N. 0°23.2' E., on the N-S center line of the NW 1/4 of section 12.

19.981 Point for the NW 1/16 section corner of section 12, at the intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 12,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

NW 1/16 S 12

2007

Set a steel fence post along the south side of the aluminum post.

39.962 The point for the W 1/16 section corner of sections 1 and 12.

---

From the center N 1/16 section corner of section 12.

N. 89°21.4' W., on the E-W center line of the NW 1/4 of section 12.

20.068 The NW 1/16 section corner of section 12.

40.136 The point for the N 1/16 section corner of sections 11 and 12.

---

The Subdivision of Section 13,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 13 and 24.

N. 0°08.5' E., on the N-S center line of section 13.

20.027 Point for the center S 1/16 section corner of section 13, not monumented.

40.054 Point for the center 1/4 section corner of section 13 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

T 2 S R 8 W

C 1/4 S 13

2007

Set a steel fence post along the west side of the aluminum post.

A fence corner with barbed wire fences extending east and south bears N. 77° E., 62.5 ft. distance.

60.141 Point for the center N 1/16 section corner of section 13, not monumented.

80.228 The 1/4 section corner of sections 12 and 13.

---

THE SUBDIVISION OF SECTION 13,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

From the 1/4 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 89°07.0' W., on the E-W center line of section 13.

- 9.168 Intersect the center line of Utah State Road No. 196, bears NE-SW.
- 10.794 Point of intersection with the northwesterly right-of-way line (at 100 ft. offset from center line) of Utah State Road No. 196, hereinafter described.
- 20.108 Point for the center E 1/16 section corner of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{ ————— C} \\ \text{S } 13 \\ 2007 \end{array}$$

Set a steel fence post along the east side of the aluminum post.

A fence corner with fences extending north and west bears N. 49° W., 30 ft. distance.

- 40.216 The center 1/4 section corner of section 13.
- 60.267 Point for the center W 1/16 section corner of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{ ————— C} \\ \text{S } 13 \\ 2007 \end{array}$$

Set a steel fence post along the west side of the aluminum post.

Found a mound of stone, 3 ft. base, 1 1/2 ft. high, bears N. 36 1/2° W., 6.5 ft. distance, under an old barbed wire fence, bears east and west.

- 80.318 The 1/4 section corner of sections 13 and 14.

From the center E 1/16 section corner of section 13.

N. 0°03.0' E., on the N-S center line of the NE 1/4 of

THE SUBDIVISION OF SECTION 13,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

section 13.

- 20.040 Point for the NE 1/16 section corner of section 13, at the intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 30 inches in the ground, with aluminum cap marked:

NE 1/16 S 13

2007

A fence corner with fences extending north, south, and east bears S. 17° W., 15.9 ft. distance.

- 40.080 The point for the E 1/16 section corner of sections 12 and 13.

---

From the N 1/16 section corner of sections 13 and 18, on the east boundary of the township, hereinbefore described.

N. 88°58.7' W., on the E-W center line of the NE 1/4 of section 13.

- 0.975 Intersect the center line of Utah State Road No. 196, bears NE-SW.

- 2.600 Point of intersection with the northwesterly right-of-way line (at 100 ft. offset from center line) of Utah State Road No. 196, hereinafter described.

- 20.076 The NE 1/16 section corner of section 13.

- 40.152 The point for the center N 1/16 section corner of section 13.

---

From the E 1/16 section corner of sections 13 and 24.

N. 0°07.9' E., on the N-S center line of the SE 1/4 of section 13.

- 11.182 Point of intersection with the southeasterly right-of-way line (at 50 ft. offset from center line) of Utah State Road No. 196, hereinafter described.

- 13.186 Intersect the center line of Utah State Road No. 196, bears NE-SW.

- 17.188 Point of intersection with the northwesterly right-of-way line (at 100 ft. offset from center line) of Utah State Road No. 196, hereinafter described.

- 40.092 The center east 1/16 section corner of section 13.

THE SUBDIVISION OF SECTION 13,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

---

From the W 1/16 section corner of sections 13 and 24.

N. 0°13.8' E., on the N-S center line of the SW 1/4 of section 13.

20.049 Point for the SW 1/16 section corner of section 13, at the intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

SW 1/16 S 13

2007

Corner is located under a N-S barbed wire fence, 7.5 ft. south of a fence corner with barbed wire fences extending west and south.

40.098 The center W 1/16 section corner of section 13.

---

From the point for the center S 1/16 section corner of section 13.

N. 89°11.1' W., on the E-W center line of the SW 1/4 of section 13.

20.083 The SW 1/16 section corner of section 13.

40.166 The S 1/16 section corner of sections 13 and 14.

---

From the center W 1/16 section corner of section 13.

N. 0°13.3' E., on the N-S center line of the NW 1/4 of section 13.

40.105 The W 1/16 section corner of sections 12 and 13.

---

The Subdivision of Section 23,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 23 and 26.

N. 0°33.9' E., on the N-S center line of section 23.

19.894 Point for the center S 1/16 section corner of section 23.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 23,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

C  
S 1/16 | S 23  
C  
2007

Corner is located at a fence corner with barbed wire fences extending north and east.

39.788 Point for the center 1/4 section corner of section 23 at the intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 8 W

C 1/4 S 23

2007

Corner is located at a fence corner with barbed wire fences extending north, south, and east.

79.943 The 1/4 section corner of sections 14 and 23.

---

From the 1/4 section corner of sections 23 and 24.

S. 89°52.5' W., on the E-W center line of section 23.

19.992 Point for the center E 1/16 section corner of section 23, not monumented.

39.984 The center 1/4 section corner of section 23.

79.662 The 1/4 section corner of sections 22 and 23.

---

From the E 1/16 section corner of sections 23 and 26.

N. 0°24.3' E., on the N-S center line of the SE 1/4 of section 23.

20.006 Point for the SE 1/16 section corner of section 23, at the intersection with the E-W center line of the SE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 28 inches in the ground, with aluminum cap marked:

SE 1/16 S 23

2007

THE SUBDIVISION OF SECTION 23,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located at a fence corner with barbed wire fences extending east, west, and south.

40.012 The point for the center E 1/16 section corner of section 23.

---

From the point for the S 1/16 section corner of sections 23 and 24.

N. 89°48.0' W., on the E-W center line of the SE 1/4 of section 23.

20.048 The SE 1/16 section corner of section 23.

40.096 The center S 1/16 section corner of section 23.

---

The Subdivision of Section 24,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 24 and 25.

N. 0°10.5' W., on the N-S center line of section 24.

20.134 Point for the center S 1/16 section corner of section 24.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, with aluminum cap marked:

C  
S 1/16 | S 24  
C  
2007

Set a steel fence post along the SE side the aluminum post.

40.268 Point for the center 1/4 section corner of section 24 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
C 1/4 S 24

2007

Set a steel fence post along the east side of the aluminum

THE SUBDIVISION OF SECTION 24,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

post.

From this corner, the United States Coast and Geodetic Survey Benchmark "G87", set in 1934, bears N. 52°07.9' W., 3.408 chains distance, monumented with a standard brass disk, 3 1/2 inches in diameter, seated in a concrete monument, 10 inches square, projecting 6 inches above the ground, marked G 87 1934.

- 42.657 Point of intersection with the southeasterly right-of-way line (at 50 ft. offset from center line) of Utah State Road No. 196, hereinafter described.
- 44.645 Intersect the center line of Utah State Road No. 196, bears NE-SW.
- 80.527 The 1/4 section corner of sections 13 and 24.

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township, hereinbefore described.

N. 89°03.3' W., on the E-W center line of section 24.

- 20.024 Point for the center E 1/16 section corner of section 24.
- Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 10 inches in the ground to solid rock, in a mound of stone, 3 ft. base to top, with aluminum cap marked:

E 1/16  
C ————— C  
S 24  
2007

Set a steel fence post along the west side of the aluminum post.

- 40.048 The center 1/4 section corner of section 24.
- 41.850 Intersect the center line of Utah State Road No. 196, bears NE-SW.
- 60.322 Point for the center W 1/16 section corner of section 24, not monumented.
- 80.596 The 1/4 section corner of sections 23 and 24.

From the center E 1/16 section corner of section 24.

N. 0°02.4' W., on the N-S center line of the NE 1/4 of section 24.



THE SUBDIVISION OF SECTION 24,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

40.241 The E 1/16 section corner of sections 13 and 24.

---

From the W 1/16 section corner of sections 24 and 25.

N. 0°02.2' E., on the N-S center line of the SW 1/4 of section 24.

20.126 Point for the SW 1/16 section corner of section 24, at the intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

SW 1/16 S 24

2007

Set a steel fence post along the east side of the aluminum post.

Corner is located 44 ft. south of a barbed wire fence, bears east and west.

40.252 The point for the center W 1/16 section corner of section 24.

---

From the center S 1/16 section corner of section 24.

N. 89°02.3' W., on the E-W center line of the SW 1/4 of section 24.

10.085 Intersect the center line of Utah State Road No. 196, bears NE-SW.

20.349 The SW 1/16 section corner of section 24.

40.698 The point for the S 1/16 section corner of sections 23 and 24.

---

The Subdivision of Section 25,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 25 and 36.

N. 0°31.1' E., on the N-S center line of section 25.

40.190 Point for the center 1/4 section corner of section 25 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 25,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 2 S R 8 W

C 1/4 S 25

2007

Set a steel fence post along the SE side the aluminum post.

80.386 The 1/4 section corner of sections 24 and 25.

---

From the 1/4 section corner of sections 25 and 30, on the east boundary of the township, hereinbefore described.

N. 89°19.4' W., on the E-W center line of section 25.

40.116 The center 1/4 section corner of section 25.

60.440 Point for the center W 1/16 section corner of section 25.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

W 1/16  
C ————— C  
S 25  
2007

Set a steel fence post along the east side of the aluminum post.

Corner is located 61 ft. north of the center line of a dirt road, bears east and west.

74.614 Intersect the center line of Utah State Road No. 196, bears NE-SW.

80.764 The 1/4 section corner of sections 25 and 26.

---

From the center W 1/16 section corner of section 25.

N. 0°22.4' E., on the N-S center line of the NW 1/4 of section 25.

35.189 Intersect the center line of Utah State Road No. 196, bears NE-SW.

40.306 The W 1/16 section corner of sections 24 and 25.

THE SUBDIVISION OF SECTION 35,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

---

The Subdivision of Section 35,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 2 and 35, on the south boundary of the township, hereinbefore described.

N. 0°05.8' E., on the N-S center line of section 35.

20.484 Point for the center S 1/16 section corner of section 35.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 26 inches in the ground, with aluminum cap marked:

C  
|  
S 1/16      S 35  
|  
C  
2007

Set a steel fence post along the north side of the aluminum post.

40.968 Point for the center 1/4 section corner of section 35 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 29 inches in the ground, with aluminum cap marked:

T 2 S R 8 W  
  
C 1/4      S 35  
  
2007

Set a steel fence post along the north side of the aluminum post.

61.110 Point for the center N 1/16 section corner of section 35.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

C  
|  
N 1/16      S 35  
|  
C  
2007

Set a steel fence post along the north side of the aluminum

THE SUBDIVISION OF SECTION 35,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

post.

81.252 The 1/4 section corner of sections 26 and 35.

---

From the 1/4 section corner of sections 35 and 36.

S. 89°57.0' W., on the E-W center line of section 35.

19.975 Point for the center E 1/16 section corner of section 35, not monumented.

35.322 Intersect the center line of Utah State Road No. 196, bears NE-SW.

37.061 Point of intersection with the northwesterly right-of-way line (at 100 ft. offset from center line) of Utah State Road No. 196, hereinafter described.

39.950 The center 1/4 section corner of section 35.

59.997 Point for the center W 1/16 section corner of section 35, not monumented.

80.044 The 1/4 section corner of sections 34 and 35.

---

From the point for the center E 1/16 section corner of section 35.

N. 0°07.0' E., on the N-S center line of the NE 1/4 of section 35.

20.150 Point for the NE 1/16 section corner of section 35, at the intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 30 inches in the ground, with aluminum cap marked:

NE 1/16 S 35

2007

Set a steel fence post along the east side of the aluminum post.

Corner is located 153.7 ft. east of a barbed wire fence, bears NE-SW.

24.277 Point of intersection with the southeasterly right-of-way line (at 100 ft. offset from center line) of Utah State Road No. 196, hereinafter described.

27.379 Intersect the center line of Utah State Road No. 196, bears

THE SUBDIVISION OF SECTION 35,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

NE-SW.

- 30.480 Point of intersection with the northwesterly right-of-way line (at 100 ft. offset from center line) of Utah State Road No. 196, hereinafter described.
- 40.300 The E 1/16 section corner of sections 26 and 35.

From the point for the N 1/16 section corner of sections 35 and 36.

S. 89°55.7' W., on the E-W center line of the NE 1/4 of section 35.

- 19.981 The NE 1/16 section corner of section 35.
- 22.295 Point of intersection with the southeasterly right-of-way line (at 100 ft. offset from center line) of Utah State Road No. 196, hereinafter described.
- 24.033 Intersect the center line of Utah State Road No. 196, bears NE-SW.
- 25.771 Point of intersection with the northwesterly right-of-way line (at 100 ft. offset from center line) of Utah State Road No. 196, hereinafter described.
- 39.962 The center N 1/16 section corner of section 35.

From the W 1/16 section corner of sections 2 and 35, on the south boundary of the township, hereinbefore described.

N. 0°10.7' E., on the N-S center line of the SW 1/4 of section 35.

- 20.284 Point for the SW 1/16 section corner of section 35, at the intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with aluminum cap marked:

SW 1/16 S 35

2007

Set a steel fence post along the east side of the aluminum post.

- 40.568 The point for the center W 1/16 section corner of section 35.

From the center S 1/16 section corner of section 35.

THE SUBDIVISION OF SECTION 35,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 89°28.9' W., on the E-W center line of the SW 1/4 of section 35.

20.077 The SW 1/16 section corner of section 35.

40.154 The point for the S 1/16 section corner of sections 34 and 35.

---

The Dependent Resurvey of a Portion of the Right-of-Way  
Lines of Utah State Road No. 196,  
Township 2 South, Range 8 West, Salt Lake Meridian, Utah

---

Reestablishment of the Right-of-Way Survey Executed by  
the State of Utah in 1951, Project AD-1.

---

**Note:** The right-of-way lines of Utah State Road No. 196 (SR 196), are determined by dependent resurvey of existing survey markers set in 1951 by the Utah Department of Transportation (UDOT), Project AD-1. All stations cited herein refer to stationing labels on the official drawing sheets of said Project AD-1, on file at UDOT.

From the northwesterly right-of-way line marker at Station No. 1410+00 of SR 196, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,

from which

The southeasterly right-of-way line marker bears S.60°39.8'E., 3.030 chains distance, monumented with an iron post, 2 inches in diameter, firmly set 2 ft. SE of a NE-SW barbed wire fence line, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY.

N. 29°21.5' E., on the northwesterly right-of-way line of SR 196.

1.002 The point at the intersection with the E-W center line of section 35, not monumented.

15.157 The northwesterly right-of-way line marker at Station No. 1420+00 of SR 196, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,

from which

THE DEPENDENT RESURVEY OF A PORTION OF THE RIGHT-OF-WAY  
LINES OF UTAH STATE ROAD No. 196,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The southeasterly right-of-way line marker bears S.60°44.5'E., 3.026 chains distance, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 29°20.8' E., beginning new measurement.

8.971 The point at the intersection with the E-W center line of the NE 1/4 of section 35, not monumented.

15.149 The northwesterly right-of-way line marker at Station No. 1430+00 of SR 196, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,

from which

The southeasterly right-of-way line marker bears S.60°42.1'E., 3.028 chains distance, monumented with an iron post, 2 inches in diameter, firmly set, under a NE-SW barbed wire fence, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 29°20.6' E., beginning new measurement.

5.680 The point at the intersection with the N-S center line of the NE 1/4 of section 35, not monumented.

16.956 The point at the intersection with the line between sections 26 and 35, not monumented.

25.618 The northwesterly right-of-way line marker at a point of circular curvature (P.C.), Station No. 1446+90.8, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,

from which

The southeasterly right-of-way line marker bears S. 60°48.7' E., 3.028 chains distance, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY.

---

THE DEPENDENT RESURVEY OF A PORTION OF THE RIGHT-OF-WAY  
LINES OF UTAH STATE ROAD NO. 196,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

From the southeasterly right-of-way line marker at Station No. 1420+00 of SR 196.

**N. 29°21.2' E.**, on the southeasterly right-of-way line of SR 196.

- 10.674** The point at the intersection with the E-W center line of the NE 1/4 of section 35, not monumented.
- 15.147** The southeasterly right-of-way line marker at Station No. 1430+00 of SR 196.

---

**N. 29°20.4' E.**, beginning new measurement.

- 0.265** The point at the intersection with the N-S center line of the NE 1/4 of section 35, not monumented.
- 18.663** The point at the intersection with the line between sections 26 and 35, not monumented.
- 25.625** The southeasterly right-of-way line marker at a point of circular curvature (P.C.), Station No. 1446+90.8.

---

From the point on the southeasterly right-of-way line, on a projection S. 22°20.9' W., from Station No. 1550+00 through Station No. 1540+00, (at 50 ft. offset from center line) of SR 196, at the intersection with the N-S center line of section 24, not monumented.

**N. 22°20.9' E.**, on the southeasterly right-of-way line of SR 196.

- 14.879** The southeasterly right-of-way line marker at Station No. 1540+00 of SR 196, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,

from which

The northwesterly right-of-way line marker bears N. 67°40.5' W., 1.520 chains distance, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY.

- 30.017** The southeasterly right-of-way line marker at Station No. 1550+00 of SR 196, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,



THE DEPENDENT RESURVEY OF A PORTION OF THE RIGHT-OF-WAY  
LINES OF UTAH STATE ROAD No. 196,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

from which

The northwesterly right-of-way line marker bears N. 67°50.2' W., 1.516 chains distance, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 22°21.2' E., beginning new measurement.

10.636 The point at the intersection with the line between sections 13 and 24, not monumented.

15.133 The southeasterly right-of-way line marker at Station No. 1560+00 of SR 196, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,

from which

The northwesterly right-of-way line marker bears N. 67°31.1' W., 1.518 chains distance, monumented with an iron post, 2 inches in diameter, firmly set, projecting 4 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY.

22.641 The point at the intersection with the N-S center line, on a projection N. 22°21.2' E., from Station No. 1540+00 through Station No. 1550+00 (at 50 ft. offset from center line) of the SE 1/4 of section 13, not monumented.

---

From the point on the northwesterly right-of-way line, on a projection S. 22°22.0' W., from Station No. 1590+00 through Station No. 1580+00, (at an offset of 100 ft. from the center line) of SR 196, and at the intersection with the N-S center line of the SE 1/4 of section 13, not monumented.

N. 22°22.0' E., on the northwesterly right-of-way line of SR 196.

17.221 The northwesterly right-of-way line marker at Station No. 1580+00 of SR 196, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,

from which

The southeasterly right-of-way line marker bears S. 67°41.4' E.,

THE DEPENDENT RESURVEY OF A PORTION OF THE RIGHT-OF-WAY  
LINES OF UTAH STATE ROAD No. 196,  
TOWNSHIP 2 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

3.026 chains distance, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY.

24.613 The point at the intersection with the E-W center line of section 13, not monumented.

32.362 The northwesterly right-of-way line marker at Station No. 1590+00 of SR 196, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,

from which

The southeasterly right-of-way line marker bears S. 67°39.8' E., 3.028 chains distance, monumented with an iron post, 2 inches in diameter, firmly set, projecting 6 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY.

---

N. 22°22.1' E., beginning new measurement.

13.741 The point at the intersection with the E-W center line of the NE 1/4 of section 13, not monumented.

15.134 The northwesterly right-of-way line marker at Station No. 1600+00 of SR 196, monumented with an iron post, 2 inches in diameter, firmly set under a NE-SW fence line, projecting 4 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY,

from which

The southeasterly right-of-way line marker bears S. 67°44.3' E., 3.028 chains distance, monumented with an iron post, 2 inches in diameter, firmly set, projecting 8 inches above a concrete pillar, 10 inches in diameter, with brass cap, 3 inches in diameter, marked: STATE ROAD RIGHT OF WAY

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Calvert C. Norton	Survey Technician
Adrian M. Kurip	Survey Technician

---

## CERTIFICATE OF SURVEY

We, *Ronald K. Baugh, Supervisory Cadastral Surveyor, and Daniel T. Gillins, Survey Technician*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *28<sup>th</sup> day of August, 2007*, have *dependently resurveyed a portion of the south, east, and north boundaries, and a portion of the subdivisional lines, subdivided sections 12, 13, 23, 24, 25, and 35, and dependently resurveyed a portion of the right-of-way lines of Utah State Road No. 196, in Township 2 South, Range 8 West, of the Salt Lake Meridian, in the State of Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

*April 19, 2010*

Date

*Ronald K. Baugh*  
(Supervisory Cadastral Surveyor)

*April 19, 2010*

Date

*Daniel T. Gillins*  
(Survey Technician)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of portion of the south, east, and north boundaries, and a portion of the subdivisional lines, the subdivision of sections 12, 13, 23, 24, 25, and 35, and the dependent resurvey of a portion of the right-of-way lines of Utah State Road No. 196, in Township 2 South, Range 8 West, Salt Lake Meridian, Utah*, executed by *Ronald K. Baugh, Supervisory Cadastral Surveyor, and Daniel T. Gillins, Survey Technician*, having been critically examined and found correct, are hereby approved.

*June 11, 2010*

Date

*Daniel W. Webb*  
(Chief Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH (EIGHTH STANDARD PARALLEL SOUTH)

AND WEST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

A PORTION OF THE SUBDIVISION OF SECTION 32,

AND

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE MEANDERS OF THE RIGHT AND LEFT BANKS OF  
THE SAN JUAN RIVER,

IN

**TOWNSHIP 40 SOUTH, RANGE 24 EAST,**

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

***Scott A. Burkhardt***  
***Cadastral Surveyor***

Under Special Instructions dated and approved ***January 23, 2009***, which provided for the surveys included under Group No. ***1101***, and Assignment Instructions dated ***January 23, 2009***.

Survey Commenced, ***January 28, 2009***  
Survey Completed, ***April 1, 2009***

# INDEX DIAGRAM

Township 40 South, Range 24 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
8					
5 31	7 32	33	34	35	36
4	9 3				

Dependent Resurvey of  
The Subdivision of Section 32.....Page 9  
Meanders of the Right Bank of the San Juan River.....Page 10  
Meanders of the Left Bank of the San Juan River.....Page 12

## TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the south (Eighth Standard Parallel South) and west boundaries, a portion of the subdivisional lines, and a portion of the subdivision of sections 32, and the survey of a portion of the subdivisional lines, and the meanders of the right and left banks of the San Juan River, in Township 40 South, Range 24 East, Salt Lake Meridian, Utah.

## HISTORY OF SURVEYS

Surveyed by		Retr. Or Resurveyed by	
<b>SOUTH BOUNDARY (Eighth Standard Parallel South)</b>			
All	A.D. Ferron	1884	
Portion		H.D. Page & J.M. Lentz	1899
Portion		A. Nelson & R.C. Yundt	1953
All		M.D. Cazier	2003
All		S.A. Burkhardt	2006
<b>EAST BOUNDARY</b>			
All	A.D. Ferron	1884	
All		H.D. Page & J.M. Lentz	1899
All		M.D. Cazier	2003
<b>WEST BOUNDARY</b>			
All	A.D. Ferron	1884	
Portion		H.D. Page & J.M. Lentz	1899
Portion		A. Nelson & R.C. Yundt	1953
Portion		Donald A. Buhler	1980
All		M.D. Cazier	2003
<b>NORTH BOUNDARY</b>			
All	A.D. Ferron	1884	
All		H.D. Page & J.M. Lentz	1899
Portion		D.B. Miller & J.C. Thoma	1929
All		M.D. Cazier	2003
<b>SUBDIVISION</b>			
Portion	H.D. Page & J.M. Lentz	1899	
Portion		M.D. Cazier	2003
<b>RIGHT BANK OF THE SAN JUAN RIVER</b>			
All	H.D. Page & J.M. Lentz	1899	
<b>NAVAJO INDIAN RESERVATION BOUNDARY</b>			
All	R.C. Yundt	1944	

## TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1101, dated January 23, 2009.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods*, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic Control was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS).

The geographic positions, in NAD83 (CORS96), epoch date 2002.00 for the corners listed below were determined by Global Positioning System (GPS) observations to a Network Accuracy of less than 0.10 meter, 95 percent confidence circle, as defined in *Standards and Guidelines for Cadastral Surveys Using Global Positioning Systems Methods*, May 9, 2001, Version 1.0.

The corner of sections 25, 30, 31, and 36, on the west boundary of the Township 40 South, Range 24 East, Salt Lake Meridian, Utah is as follows:

Latitude: 37°16'23.037" N., Longitude: 109°19'52.549" W.

The 1/4 section corner of section 32 only, on the Eighth Standard Parallel South, Township 40 South, Range 24 East, Salt Lake Meridian, Utah is as follows:

Latitude: 37°15'30.895" N., Longitude: 109°18'15.657" W.



DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
(EIGHT STANDARD PARALLEL SOUTH),  
CHAINS      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

Dependent Resurvey of a Portion of the South Boundary  
(Eighth Standard Parallel South),  
Township 40 South, Range 24 East, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A.D. Ferron in 1884, the  
Dependent Resurveys Executed by H.D. Page & J.M. Lentz in 1899, A.  
Nelson & R.C. Yundt in 1953, M.D. Cazier in 2003, and S.A.  
Burkhardt in 2006.

Beginning at the standard 1/4 section corner of section 32 only, on the south boundary of the township (Eighth Standard Parallel South), monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 9 inches above the ground, with brass cap marked as described in the official record of the 2006 resurvey.

Corner is located on a grassy level field, next to fence corner for chain link fence, 6 ft. high, extends north and west.

**S. 89°57.3' W.**, on the south boundary of section 32.

- 4.668** The 1/4 section corner of section 5 only, T. 41 S., R. 24 E., monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, projecting 9 inches above a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 2006 resurvey.

Corner is located on a grassy level field, chain link fence bears 1 ft. north, extends east and west.

- 13.649** The witness corner to the meander corner of section 5 and 32, on the right bank of the San Juan River, monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 2006 resurvey.

- 19.553** Centerline of San Juan County road 450, a paved road, 24 ft. wide, bears N. 39° E., and S. 39° W.

- 24.717** True point for the meander corner of section 5 and 32, on the right bank of the San Juan River.

Reestablishment of the Survey Executed by A.D. Ferron in 1884, the  
Dependent Resurveys Executed by A. Nelson & R.C. Yundt in 1953,  
M.D. Cazier in 2003, and S.A. Burkhardt in 2006.

- 29.576** Point for the meander corner of section 5 and 32, on the left bank of the San Juan River, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
(EIGHT STANDARD PARALLEL SOUTH),  
CHAINS      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

- 39.997 Point for the Standard Corner of sections 31 and 32 only, on the south boundary of the township (Eighth Standard Parallel South), at proportionate distance. This corner was not set in previous surveys as it falls in a flood plain.

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, with brass cap marked:

SC  
T40S R24E  
S31|S32  
2009

Set a steel fence post north of corner.

Corner is located on a fairly level sandy floodplain, with cottonwood and tamarisk.

---

S. 89°57.3' W., on the south boundary of section 31.

- 4.828 The closing corner of sections 5 and 6 only, T. 41 S., R. 24 E., monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 2006 resurvey; with a steel fence post east of corner.

- 10.400 The reference monument for the 1953 resurvey, monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the 2006 resurvey.

Set a steel fence post north of corner.

- 39.999 The standard 1/4 corner of section 31 only, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 2006 resurvey.
- 

S. 89°57.1' W., beginning new measurement.

- 4.829 The 1/4 section corner of section 6 only, T. 41 S., R. 24 E., monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, projecting 2 inches above the ground, in a collar of stone, 1 1/2 ft. base, with brass cap marked as described in the official record of the 2006 resurvey; with a steel fence post north of corner.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
(EIGHT STANDARD PARALLEL SOUTH),  
CHAINS      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

- 38.701** The standard corner of T. 40 S., Rs. 23 and 24 E., monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 14 inches above the ground, with brass cap marked as described in the official record of the 2006 resurvey.

Corner is located 1 ft. south of a barbed wire fence, extends east and west.

---

Dependent Resurvey of a Portion of the West Boundary,  
Township 40 South, Range 24 East, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by A.D. Ferron in 1884, the  
Dependent Resurvey Executed by A. Nelson & R.C. Yundt in 1953, and  
M.D. Cazier in 2003.

---

From the standard corner of T. 40 S., Rs. 23 and 24 E.,  
hereinbefore described.

**N. 0°00.8' W.,** between sections 31 and 36.

- 40.009** The 1/4 section corner of sections 31 and 36, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 6 inches above the ground, in a collar of stone, 1 1/2 ft. base, with brass cap marked as described in the official record of the 2003 resurvey.

Set a steel fence post north of corner.

**N. 0°00.3' E.,** beginning new measurement.

- 7.575** Point selected for the witness corner for the meander corner of sections 31 and 36, on the left bank of the San Juan River.

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, in a collar of stone, 3 ft. base, with magnet at base, with brass cap marked:

WC  
T40S  
R23E R24E  
MC  
S36 | S31  
2009

THE DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
 CHAINS      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

Set a steel fence post north of corner.

Corner is located at the base of a steep, north-facing slope, on the south edge of the flood plain.

10.822 True point for the meander corner of sections 31 and 36, on the left bank of the San Juan River. Point falls in a location subject to erosion.

17.614 True point for the meander corner of sections 31 and 36, on the right bank of the San Juan River. Point falls in a location subject to erosion.

19.179 Point selected for the witness corner for the meander corner of sections 31 and 36, on the right bank of the San Juan River.

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 27 inches in the ground, with magnet at base, with brass cap marked:

WC  
 T40S  
 R23E R24E  
 S36 | S31  
 ↓  
 MC  
 2009

Set a steel fence post north of corner.

Corner is located on the right bank of the San Juan River, on a fairly level, sandy flood plain, in dense willow trees.

36.811 The 1953 witness corner to the meander corner of sections 31 and 36, on the right bank of the San Juan River, monumented with an iron post, 2 1/2 inches in diameter, firmly set, flush with ground surface, with brass cap marked as described in the official record of the 2003 resurvey.

Corner will now function as a witness point on the line between sections 31 and 36.

Add the marking WP 2009 to brass cap.

Corner is located on level, flat, undisturbed area in a dirt parking area, east of a gravel driveway.

---

N. 0°08.9' W., beginning new measurement.

THE DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
 CHAINS      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

- 3.199 The corner of sections 25, 30, 31, and 36, monumented with an iron post, 2 1/2 inches in diameter, firmly set, projecting 5 inches above the ground, with brass cap marked as described in the official record of the 2003 resurvey.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
 Township 40 South, Range 24 East, Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by H.D. Page & J.M. Lentz  
 in 1899, and the Dependent Resurvey Executed by M.D. Cazier in  
 2003.

---

From the meander corner of section 31 and 32, on the right bank of the San Juan River, monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, flush in a mound of stone, 4 ft. base, 1 ft. high, with brass cap marked as described in the official record of the 2003 resurvey. This corner functioned as a meander corner in the 2003 resurvey, when the San Juan River was in a different location.

This corner will now function as a witness corner to the meander corner of sections 31 and 32, on the right bank of the San Juan River, for the 2009 meander, on the section line between sections 31 and 32.

Add the markings WC 2009 to brass cap.

Corner is located on a south-facing, sand and cobble slope, near right edge of the flood plain of the San Juan River.

N. 0°03.0' W., between sections 31 and 32.

- 15.450 Point for the 1/4 section corner of sections 31 and 32, at proportionate distance, as described in the official record of the 2003 resurvey, not monumented.
- 16.136 Centerline of Utah State Highway No. 162, a paved road, 24 ft. wide, bears N. 59° W. and S. 59° E.
- 35.450 The N 1/16 section corner of sections 31 and 32, monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, flush with ground surface, with brass cap marked as described in the official record of the 2003 resurvey.

Set a steel fence post north of corner.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
*CHAINS*      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

N. 0°03.0' W., beginning new measurement.

- 19.999 The corner of sections 29, 30, 31, and 32, monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, projecting 5 inches above the ground, in a collar of stone, 2 ft. base, with brass cap marked as described in the official record of the 2003 resurvey; with a steel fence post north of corner.
- 

S. 89°49.3' W., between sections 30 and 31.

- 20.090 The E 1/16 section corner of sections 30 and 31, monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 2003 resurvey; with a steel fence post north of corner.
- 

S. 89°49.1' W., beginning new measurement.

- 20.087 The 1/4 section corner of sections 30 and 31, monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, projecting 2 inches above the ground, with brass cap marked as described in the official record of the 2003 resurvey.

Set a steel fence post north of corner.

---

S. 89°49.2' W., beginning new measurement.

- 37.788 Centerline of Utah State Highway No. 162, a paved road, 24 ft. wide, bears N. 65° W. and S. 65° E.

- 40.086 The corner of sections 25, 30, 31, and 36, on the west boundary of the township, hereinbefore described.
- 

Dependent Resurvey of a Portion of the Subdivision of Section 32,  
 Township 40 South, Range 24 East, Salt Lake Meridian, Utah

---

From the 1/4 section corner of section 32 only, on the south boundary of the township (Eighth Standard Parallel South), hereinbefore described.

N. 0°09.1' E., on the N-S centerline of section 32.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 32,  
 CHAINS      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

- 13.331 Centerline of Utah State Highway No. 162, a paved road, 24 ft. wide, bears N. 69° W. and S. 69° E.
- 20.003 The point for the center S 1/16 section corner of section 32, at proportionate distance, not monumented.
- 33.817 Centerline of Utah State Highway No. 262, a paved road, 24 ft. wide, bears N. 27° E. and S. 27° W.
- 40.006 The center 1/4 section corner of section 32, monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 2003 resurvey; with a steel fence post to the SW.

N. 89°43.0' W., on the E-W centerline of section 32.

- 19.235 The center W 1/16 section corner of section 32, monumented with a stainless steel post, 2 1/2 inches in diameter, firmly set, projecting 7 inches above the ground, with brass cap marked as described in the official record of the 2003 resurvey.

N. 89°46.5' W., beginning new measurement.

- 18.140 Centerline of U.S. Highway 161, a paved road, 24 ft. wide, bears N. 59° W. and S. 59° E.
- 19.266 The point for the 1/4 section corner of sections 31 and 32.

The Survey of a Portion of the Subdivisional Lines,  
 Township 40 South, Range 24 East, Salt Lake Meridian, Utah

From the standard corner of sections 31 and 32, on the south boundary of the township (Eighth Standard Parallel South), hereinbefore described.


N. 3°43.6' E., between sections 31 and 32.

- 17.671 Point selected for the witness corner for the meander corner of sections 31 and 32, on the left bank of the San Juan River.

Set a stainless steel post, 30 inches long, 2 1/2 inches in diameter, 25 inches in the ground, in a collar of stone, 3 ft.

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
 CHAINS      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

base, with magnet at base, with brass cap marked:

WC  
 T40S R24E  
 MC  
  
 S31 | S32  
 2009

Set a steel fence post north of the stainless steel post.

Corner is located on a fairly level, sandy flood plain, with cottonwood and tamarisk.

- 19.066 True point for the meander corner of sections 31 and 32, on the left bank of the San Juan River. Point falls in a location subject to erosion.
- 22.368 True point for the meander corner of sections 31 and 32, on the right bank of the San Juan River. Point falls in a location subject to erosion.
- 24.811 The witness corner to the meander corner of sections 31 and 32, on the right bank of the San Juan River, hereinbefore described.

---

The Survey of the Meanders of the Right Bank  
 of the San Juan River,  
 Township 40 South, Range 24 East, Salt Lake Meridian, Utah

---

From the true point for the meander corner of sections 5 and 32, on the right bank of the San Juan River, on the Eighth Standard Parallel South, hereinbefore described.

Thence, downstream with the meanders of the present right bank of the San Juan River, through section 32.

N. 27°22.5' W., 3.560 Chains  
 N. 13°37.5' W., 3.427 Chains  
 N. 0°35.4' W., 5.007 Chains  
 N. 39°08.0' W., 1.977 Chains  
 N. 56°35.4' W., 1.092 Chains  
 N. 29°23.0' W., 2.515 Chains  
 N. 51°06.2' W., 3.763 Chains  
 N. 43°45.1' W., 1.977 Chains  
 N. 49°10.3' W., 3.794 Chains



THE SURVEY OF THE MEANDERS OF THE RIGHT BANK OF  
THE SAN JUAN RIVER,  
CHAINS      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

N. 74°33.6' W., 0.800 Chains      The true point for the meander  
corner of sections 31 and 32,  
hereinbefore described.

Thence, in section 31.

N. 81°20.2' W., 1.367 Chains  
N. 48°30.4' W., 0.747 Chains  
N. 72°31.0' W., 1.986 Chains  
N. 79°50.1' W., 5.414 Chains  
N. 87°51.9' W., 4.717 Chains  
S. 75°21.3' W., 5.001 Chains  
S. 67°35.4' W., 3.752 Chains  
S. 58°19.1' W., 2.727 Chains  
S. 72°27.8' W., 1.369 Chains  
N. 71°02.4' W., 2.175 Chains  
N. 38°45.5' W., 4.973 Chains  
N. 24°13.5' W., 1.578 Chains  
N. 45°44.0' W., 2.464 Chains  
N. 36°46.3' W., 6.114 Chains  
N. 45°50.9' W., 5.702 Chains  
N. 64°04.9' W., 5.434 Chains  
N. 77°58.8' W., 1.929 Chains  
N. 57°14.3' W., 3.476 Chains  
N. 51°18.6' W., 14.271 Chains  
N. 60°17.1' W., 11.177 Chains  
N. 74°22.0' W., 4.222 Chains  
N. 83°49.4' W., 4.455 Chains

The true point for the meander  
corner of sections 31 and 36, on  
the west boundary of the  
township, hereinbefore described.

The Survey of the Meanders of the Left Bank  
of the San Juan River,  
Township 40 South, Range 24 East, Salt Lake Meridian, Utah

From the point for the meander corner of sections 5 and 32, on the  
left bank of the San Juan River, on the Eighth Standard Parallel  
South, hereinbefore described.

Thence, downstream with the meanders of the present left bank of

THE SURVEY OF THE MEANDERS OF THE LEFT BANK  
OF THE SAN JUAN RIVER,  
CHAINS      TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

the San Juan River, through section 32.

N. 18°54.7' W., 6.927 Chains  
N. 4°12.0' E., 3.122 Chains  
N. 6°07.8' W., 3.992 Chains  
N. 45°50.6' W., 3.250 Chains  
N. 61°21.2' W., 1.720 Chains  
N. 51°39.5' W., 3.693 Chains

The true point for the meander  
corner of sections 31 and 32.

Thence, in section 31.

N. 59°50.6' W., 3.426 Chains  
N. 74°22.9' W., 4.971 Chains  
N. 85°01.3' W., 4.040 Chains  
S. 84°34.1' W., 2.051 Chains  
S. 72°42.3' W., 5.038 Chains  
S. 65°46.9' W., 2.058 Chains  
S. 54°58.2' W., 5.559 Chains  
N. 82°22.9' W., 1.723 Chains  
N. 55°06.9' W., 1.491 Chains  
N. 46°12.8' W., 5.583 Chains  
N. 54°16.0' W., 5.110 Chains  
N. 51°09.1' W., 3.677 Chains  
N. 69°31.9' W., 1.292 Chains  
N. 59°52.5' W., 4.040 Chains  
N. 51°22.2' W., 4.979 Chains  
N. 35°59.0' W., 1.533 Chains  
N. 40°51.3' W., 3.496 Chains  
N. 6°55.9' W., 0.888 Chains  
N. 47°38.1' W., 3.254 Chains  
N. 45°25.0' W., 4.025 Chains  
N. 63°52.8' W., 2.932 Chains  
N. 43°46.9' W., 2.736 Chains  
N. 68°56.8' W., 5.984 Chains  
S. 72°19.9' W., 1.396 Chains  
N. 83°01.1' W., 2.633 Chains  
N. 47°43.9' W., 1.217 Chains

THE SURVEY OF THE MEANDERS OF THE LEFT BANK  
OF THE SAN JUAN RIVER,  
*CHAINS* TOWNSHIP 40 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

N. 82°05.6' W., 6.215 Chains

N. 60°59.5' W., 3.021 Chains

The true point for the meander  
corner of sections 31 and 36, on  
the west boundary of the  
township, hereinbefore described.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Phil Freiberg	Survey Technician

---

## CERTIFICATE OF SURVEY

I, Scott A. Burkhardt, **Cadastral Surveyor**, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the 23rd day of **January, 2009**, I have **dependently resurveyed a portion of the south (Eighth Standard Parallel South) and west boundaries, a portion of the subdivisional lines, and a portion of the subdivision of section 32, and the survey of the meanders of the right and left banks of the San Juan River, in Township 40 South, Range 24 East, of the Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

4/19/2010

Date

Scott A. Burkhardt

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the south (Eighth Standard Parallel South) and west boundaries, a portion of the subdivisional lines, and a portion of the subdivision of section 32, and the survey of the meanders of the right and left banks of the San Juan River, in Township 40 South, Range 24 East, Salt Lake Meridian, Utah**, executed by **Scott A. Burkhardt, Cadastral Surveyor**, having been critically examined and found correct, are hereby approved.

April 20, 2010

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)